

DECLARATION OF PERFORMANCE
DoP No. 102.004 (EN)



- 1. Unique identification code of the product-type:**
(102.004) LENA 2 FLEX White
- 2. Intended Use(s):**
(C2TE) Cementitious adhesive for internal and external tiling on floors and walls
- 3. Manufacturer:**
LENARGATECNIC, LDA.
Rua dos Castanheiros, 11 Boa Vista
2420-415 Leiria – Portugal
Trade name: ARGATECNIC
Tel: (+351) 244 723 720 | Email: geral@argatecnic.pt | www.argatecnic.pt
- 4. System of assessment and verification of constancy of performance (AVCP):**
System 3
- 5. Harmonised standard:**
EN 12004:2007+A1:2012

Notified body:

CTCV - Centro Tecnológico da Cerâmica e do Vidro, notified body no. 0855, has performed the determination of the product-type on the basis of type testing under system 3 and issued the respective report.

6. Declared performance:

| Essential Characteristics | Performance | Harmonised Technical Specification |
|--|-------------------------|------------------------------------|
| Reaction to fire | Class E (CWFT) | EN 12004:2007+A1:2012 |
| Initial tensile adhesion strength | ≥ 1,0 N/mm ² | EN 12004:2007+A1:2012 |
| Tensile adhesion strength after heat ageing | ≥ 1,0 N/mm ² | EN 12004:2007+A1:2012 |
| Tensile adhesion strength after water immersion | ≥ 1,0 N/mm ² | EN 12004:2007+A1:2012 |
| Tensile adhesion strength after freeze-thaw cycles | ≥ 1,0 N/mm ² | EN 12004:2007+A1:2012 |
| Open time (after 30 min) | ≥ 0,5 N/mm ² | EN 12004:2007+A1:2012 |
| Slip | ≤ 0,5 mm | EN 12004:2007+A1:2012 |
| Release of dangerous substances | See MSDS | - |

MSDS – Material safety data sheet

- 7. The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.**

Signed for and on behalf of the manufacturer by:


Michael Franco (Manager)

Boa Vista, 1st September, 2022