

**DECLARATION OF PERFORMANCE**  
**DoP No. 102.003 (EN)**



- 1. Unique identification code of the product-type:**  
(102.003) LENA 2 FLEX Gray
- 2. Intended Use(s):**  
(C2TE) Cementitious adhesive for internal and external tiling on floors and walls
- 3. Manufacturer:**  
LENARGATECNIC, LDA.  
Rua dos Castanheiros, 11 Boa Vista  
2420-415 Leiria – Portugal  
**Trade name:** ARGATECNIC  
Tel: (+351) 244 723 720 | Email: geral@argatecnic.pt | www.argatecnic.pt
- 4. System of assessment and verification of constancy of performance (AVCP):**  
System 3
- 5. Harmonised standard:**  
EN 12004:2007+A1:2012

**Notified body:**

CTCV - Centro Tecnológico da Cerâmica e do Vidro, notified body no. 0855, has performed the determination of the product-type on the basis of type testing under system 3 and issued the respective report.

**6. Declared performance:**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E (CWFT)	EN 12004:2007+A1:2012
Initial tensile adhesion strength	≥ 1,0 N/mm <sup>2</sup>	EN 12004:2007+A1:2012
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm <sup>2</sup>	EN 12004:2007+A1:2012
Tensile adhesion strength after water immersion	≥ 1,0 N/mm <sup>2</sup>	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm <sup>2</sup>	EN 12004:2007+A1:2012
Open time (after 30 min)	≥ 0,5 N/mm <sup>2</sup>	EN 12004:2007+A1:2012
Slip	≤ 0,5 mm	EN 12004:2007+A1:2012
Release of dangerous substances	See MSDS	-

MSDS – Material safety data sheet

- 7. The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.**

Signed for and on behalf of the manufacturer by:

  
Michael Franco (Manager)

Boa Vista, 1<sup>st</sup> September, 2022